

CET33

Professional grade vinyl electrical tape

All weather, professional grade, pressure sensitive vinyl tape which applies easily and gives excellent performance over a wide range of temperatures. Cold and weather resistant. Flame retardant. CET33 can be used as primary insulation for splices up to 600 volts. Use as protective outer jacket over splices and for all low temperature applications.

Features And Benefits

- 7 mil thickness
- Cold and weather resistant
- High dielectric strength
- Highly elastic
- Flame retardant
- Highly resistant to sun, water, oil, acids, alkalies, corrosive chemicals
- Lead free

Standards

- ASTM D 3005, Type I
- ASTM D 1000
- HH-I-595C/A-A-55809A
- EN 60454-3-1, Type 11
- UL 510
- CSA C22.2 no.197

Typical Applications

- General splicing purposes
- Primary insulation for splices up to 600 volts
- Provides a protective outer jacket over splices for all low temperature applications
- Wrapping wire harnesses, and insulating degaussing coils

Ordering

- Please specify the product name/order reference number.
- Order Example: CET33



Storage

- Store the product in its original packaging in a clean dry place and placed in a horizontal position under cover in temperature conditions between 5°C to 35°C (41°F to 95°F).
- Stock rotation is recommended.

ORDER NUMBER	COLOR	THICKNESS		WIDTH		LENGTH	
		MM	IN	MM	IN	M	FT
CET33	Black	0.18	0.007	19	0.75	20	66

Additional sizes available upon request

Version: